

ADesignStudio.



EON 11 CHANDELIER 4.250.7150.4.60

Designed by Alex Fitzpatrick

FITTING TYPE
SUSPENDED

CONSTRUCTION
GLASS, ALUMINIUM, STEEL, NYLON

GLASS
x4 250mm Dia Clear Crackle Glass
x7 150mm Dia Clear Crackle Glass
x4 60mm Dia Clear Glass

UPLIGHT SPECIFICATION
Source: x22 LED [x1 LED each (Vf 3V)]
Power: 50W Indirect [Each 2.1W @ 700mA
Constant Current
Output: Ambient
Colour Temperature: 2700K
Colour Rendering Index: CRI90+ 2-step Binning

DIRECT LIGHTING SPECIFICATION
Source: x4 Spots [x1 LED each (Vf 3V)]
Power: Each 2.1W @ 700mA Constant Current
Output: Wide beam
Colour Temperature: 2700K
Colour Rendering Index: CRI90+ 2-step Binning

CONTROL
x2 Remote Driver DALI -
Channel 1 to control the downlights
Channel 2 to control the uplights.

CORD
8mm power cable. 1.5mm stainless steel wire

WEIGHT
≈ 35KG

DIMENSIONS
1780mm L x 500mm W x 250mm H
Drop Height 1800mm

